Flammability Certificate 3171 Boucle Melange

3171 Boucle Melange was tested and met the following flammability requirements:

CA TB 117-2013



719 century ave sw • grand rapids, mi 49503 e. info@flooralytics.com p. 616.369.0522



report number est-2332 revision level original report date 3.13.2023

certificate of testing

Designtex client

357 County Ave

Secaucus, NJ 07094

product identification Boucle Melange 3171

test method performed smolder resistance of materials used in upholstered furniture – section 1: cover fabrics

california technical bulletin 117: 2013 (january 2019 revision)

date of test 3.13.2023

test results

specimen	char length (in.)	extinguished <45 min (y/n)
1	0.4	У
2	self-extinguished	У
3	0.4	V

notes

test conditions 70 ±3.5°f, 50 ±5% relative humidity requirement: 21 ±3°c, less than 55% relative humidity

sampling as received ignition source srm1196a deviations none

acceptance criteria

vertical char length ≤1.8 inches (45mm) pass

- smoldering extinguishes within 45 minutes
- no transition to open flaming

vertical char > 1.8 inches (45mm) fail

- smoldering beyond 45 minutes
- specimens transition to open flaming

retest

- if only one of the three initial specimens fail, retest an additional three specimens if all three additional specimens pass the test, the cover fabric passes the test
- if any one of the additional three specimens fail, the cover fabric fails the test

classification

based upon the test results and acceptance criteria listed above, the product identified is a

 \boxtimes pass

□ fail

□ requires retesting

certification statement by signing below, the lab certifies that the results were obtained after testing specimens submitted by the client in accordance to the procedures and equipment specified by the standard stated above.



page 1 / 1 doc rev 4.15.21